

FLAX WALLPAPER-GLUE

1. short description

Norafin® flax wallpaper glue is a water-soluble adhesive paste for bonding flax wallpaper to absorbent surfaces.

2. content

100 grams

3. range

per package (à 100 g)
pasting: 7 l / 100 g 64 m²
wallpapering: 4 l / 100 g 16 m²

Note:

The flax wallpaper glue can be used as a primer for „pre-pasting“ before wallpapering.

4. color

transparent

5. thinner

water

6. drying time

does not apply

7. areas of application

for gluing flax wallpaper on absorbent surfaces

8. properties

Norafin® flax wallpaper glue is very efficient; the breathability of the underlying surface is maintained.

9. processing notes

9.1 preparation

The surfaces must be solid, dry, clean, dust-free and absorbent. Uneven surfaces must be filled and levelled. Old wallpaper, woodchip residue etc. have to be removed or checked for strength and absorbency. Glue paints as well as loose oil and binder coats must be removed completely. Oil and binder coats that are still firm must be mechanically roughened to create an absorbent surface. Highly absorbent surfaces must be pre-pasted.

9.2 processing

Norafin® wallpaper glue is to be sprinkled into water while stirring continuously until a lump-free mass has formed. Warm water facilitates the dissolving process. After a swelling time of approx. 40–60 minutes, the Norafin® flax wallpaper glue should be stirred thoroughly once more. Afterwards, the mixture is ready for use. The Norafin® flax wallpaper glue is applied to the wall with a paste brush. Ensure that the glue is applied sparingly and evenly! Important: Only coat the wall with the paste, not the wallpaper! Apply the wallpaper and rub carefully to ensure an even surface. Particular care must be taken to ensure that no air pockets are created. It is recommended to press on the edges of the joints using edge rollers.

10. tools

paste brush. clean clothing and equipment with lukewarm water, wipe off glue stains with a damp cloth.

11. storage

closed, cool but frost-free.

12. composition

pure methyl celluloses of different fiber lengths. guaranteed without fungicides, preservatives or synthetic resin additives.

13. safety advice

Even natural pasting materials need to be kept out of reach of children.

14. disposal

Let glue residues dry and dispose of them according to local regulations.

Norafin 

Norafin Industries (Germany) GmbH
Gewerbegebiet Nord
309456 Mildenaue

Germany
phone: +49 (3733) 5507 0
e-mail: info@norafin.com info@mein-vlies.de

www.mein-vlies.de
www.flachstapete.de

Note:

The information in this data sheet is intended to provide technical support for distributors and users. It does not replace the test to be carried out by the user in each individual case to determine the suitability of the product and the surface (September 2017).